



# DURAM SOLVENT

CLEANING SOLVENT AND THINNERS FOR DURAM 195, MULTITHANE AND ROCKTUFF.

## Description

DURAM SOLVENT is a specific non - lacquer solvent for the thinning or diluting of Duram 195, Multithane and Rocktuff as well as cleaning and decreasing surfaces prior to the application of various products within the Duram range. Check PDS for each particular product for recommendations.

## Uses

DURAM SOLVENT is used for the thinning or diluting of Duram 195, Multithane and Rocktuff products in the Duram range of products and for the cleaning of brushes and spray equipment following the application of Duram 195, Multithane and Rocktuff. Refer to product data sheets for each particular product for more information.

## Specification

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

## Precautions in Use

Use in areas of good ventilation. The wearing of solvent resistant gloves, coveralls, mask and safety footwear is recommended. Avoid breathing vapour. Product is flammable. Keep away from naked flames and all other sources of ignition. Refer to the Material Safety Data Sheet for all precautions.

## Application

Can be applied by brush or clean cloth.  
Adhere to all precautions on MSDS.

## Coverage

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

Not Applicable.

## Colours

Clear. Available in 1 , 4 and 20 litre pails.

## Drying and Curing

Drying and curing of the product is affected by type, dryness and porosity of the surface, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

Allow product to flash off any surface that it is applied to prior to the application of another product.

## Storage

Store in cool, dry area. Product is flammable. Store away from naked flames, heat sources, other sources of ignition and any other excellerants or corrosive compounds. Keep out of the reach of children. Shelf life - about 24 months if stored correctly.

## Safety & Precautions

Read the MSDS for all precautions. Product is flammable. Class 3 dangerous goods must be declared prior to transporation. The use of a suitable mask and solvent resistant gloves, googles and coveralls is recommended when using the product.

For full safety data refer to the products Material Safety Data Sheet. Observe precautions as per label.

## Tests and Technical Data

Shelf life - about 24 months if stored correctly. Flash Point: 27 degrees C.

### CONDITIONS OF USE AND DISCLAIMER

The information contained in this data sheet is given in good faith based upon our knowledge and current information and does not imply warranty. The information is provided and the product sold on the basis that the product is used for its intended use and applied in a proper workman like manner in accordance with the instruction in this data sheet onto suitable and correctly prepared surfaces which shall remain sound, stable, free of structural defects, cracking, spalling concrete cancer, negative pressure, movement or other conditions that may effect the performance of the product. Deviations from application instructions may diminish or negate the performance of the product. Under no circumstances will the Company be liable for any loss, consequential or otherwise, arising from the use of the product. Liability is limited to the replacement of proven faulty product.

Information valid May 2018

**DURAM INDUSTRIES (PTY) LTD** ACN 002 968 809 ABN 77 002 968 809  
**The Ultimate in Waterproofing & Protective Coating Technology**

NEW SOUTH WALES: 51 Prince William Drive, Seven Hills, NSW 2147  
QUEENSLAND: Unit 4, 29 Collinsvale Street, Rocklea QLD 4106  
NEW ZEALAND: Consolidated Alloys (NZ) Ltd  
55 Maurice Rd, Penrose, Auckland, New Zealand

Tel: (02) 9624 4077 Fax: (02) 9624 4079  
Tel: (07) 3255 6478 Fax: (07) 3255 6258  
Tel: 001164 9 622 9110 Fax: 001164 9 622 9119  
Web: [www.dlmwallace.co.nz](http://www.dlmwallace.co.nz)